



Vanish EPS-2

Acidic E-Coat & Paint Stripper

EPS-2 is a Non Flammable, Non HAPS mildly acidic stripper for E-coat, Powder Coat and other difficult paints & coatings.

Effective on Ferrous and Non-Ferrous Metals. Inhibited to prevent over attack on the base metal. Highly Effective on difficult E-Coatings. Also works well for wrinkling and removing powder coating and epoxy.

Effectively lifts, wrinkles and removes cured & dried coatings from ferrous & nonferrous metals. E-Coat, Powder Coat, Epoxy, Dip Spin and Wet Coatings.

Features & Benefits

- Fast Acting
- Operates ambient up to 180 Deg. F.
- No hazardous solvents
- High solids offering cost effective stripping results.
- Provides superior results in production operations.
- No Flash Point
- Free of Formic Acid
- No Hazardous air pollutants
- Multi Metal Safe

Physical Data

pH	4.0
Product Type	Liquid
Spec. Gravity	1.07
lbs./gal.	8.92
Foam, 0 = Low, 9 = High	0
Shelf-Life Years	10 years
Freeze Information	Not damaged by freezing.

Typical Processing

1. Pour EPS into a Poly or Stainless Steel tank.
2. Heat to 120-150F



3. (Solution May be diluted up to 25% with water, Requires Agitation)
4. Immerse parts to stripped into the bath. (Poly or Stainless Baskets)
5. Allow required soaking time to lift coatings.
6. Periodic agitation will improve results.
7. Stripped parts should be subsequently washed, rinsed & Anti-rust. Contact your
8. Torch Rep. for information regarding the appropriate cleaner & inhibitor.
9. Remove paint solids from working solution to extend bath life.

Packaging

Container Type	Poly
Net Units	490
Tare Wt.	25 lb.
Gross Wt.	515
DOT_Name	Not regulated by D.O.T.
DOT Hazard	Not regulated.
Tarriff ID	

Use Parameters

Concentration Range	25-100%
Temperature Range	Ambient – 160 F.
Time Range	As required.
Agitation	Required with dilution.

Waste Disposal

Dispose of in accordance with local regulation.

Holding Tank Materials of Construction

Poly or stainless.

Other Information

It is important that the OSHA DATA, "Material Safety Data Sheet" be carefully read and reviewed with the users of this product. OSHA data is required to be posted in the work area by law.

WARRANTY: HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND



CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONDITIONS CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.

Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.